



ROTOMAKE
ENGINEERING INTERNATIONAL

AODD DIAPHRAGM PUMP

Built for Performance. Made to Last.



HIGH
PERFORMANCE



CORROSION
RESISTANT



LEAK
FREE DESIGN



EASY
MAINTENANCE



RELIABLE BY DESIGN



TRUSTED BY INDUSTRIES



MODEL	AOD 15	AOD 30	AOD 40	AOD 50	AOD 75
MOC	AL/SS/PP/ PVDF/PTFE	AL/SS/PP/ PVDF/PTFE	AL/SS/PP	AL/SS/PP	AL/SS
DIAPHRAGM	PTFE/Rubber	PTFE/Rubber	PTFE/Rubber	PTFE/Rubber	PTFE/Rubber
SUCTION & DISCHARGE	½ inch	1 inch	1 ½ inch	2 inch	3 inch
AIR INLET	¼ inch	3/8 inch	½ inch	½ inch	3/4 inch
MAX FLOW *	35 LPM	110 LPM	195 LPM	450 LPM	780 LPM
MAX DISCHARGE* PRESSURE Kg/sq. cm	4-5	5-6	4-6	4-6	6
HEAD m*	50	60	60	60	60
SUCTION LIFT	1.8 m	3.8 m	5.5 m	6.0 m	6.0 m
WEIGHT Kg	7.5/11/7	14/24/14	33/50/30	52/74/36	65/98

* (varies with MOC of pump/ diaphragm, pressure and air quantity)



APPLICATIONS

Fluid transfer, filter presses, hazardous and flameproof environments, pumping of liquids with solid particles/ slurries/ effluents, highly corrosive chemicals, solvents, acids, adhesives, paints, inks, petroleum products, diesel oil, fuel oils, plating solution, latex, oils, grouting in construction etc



www.rotomakeengineering.com | sales@rotomakeengineering.com

ROTOMAKE

AOD SERIES

Reliable air-operated pumping for demanding industrial applications.

ENGINEERED FOR PERFORMANCE

- Corrosion-resistant options
- PTFE / Rubber diaphragm options
- Multiple MOC configurations



www.rotomakeengineering.com | sales@rotomakeengineering.com