



ROTOMAKE
ENGINEERING INTERNATIONAL



PRECISION
ENGINEERED



RELIABLE
PERFORMANCE



PREMIUM
QUALITY



BUILT FOR
INDUSTRY

SEMI AUTOMATIC WEB SEALER

1.25 LTR WEB SEALER WITH SHRINK WRAPPING
| HOT KNIFE TECHNOLOGY

**ENGINEERED FOR
PERFORMANCE. BUILT
FOR RELIABILITY.**

Rotomake Semi Automatic Web Sealer is designed for efficient web sealing and shrink wrapping of bottles, cans and multipacks with precision, speed and consistency. Equipped with hot knife sealing, pneumatic actuation and variable speed drive for superior performance.



530 mm
MAX SEALING WIDTH



10 kW
CONNECTED POWER



SEMI AUTO
OPERATING MODE



VARIABLE
AC DRIVE SPEED



PRECISE SEALING
Hot knife technology ensures strong, uniform and leak proof sealing.



PNEUMATIC CONTROL
Jnatics pneumatic system for smooth and reliable operations.



VARIABLE SPEED
AC drive for variable conveyor speed to match your production needs.



CONSISTENT HEATING
Advanced temperature control for consistent shrink and seal quality.



ROTOMAKE
ENGINEERING INTERNATIONAL

PRECISION IN EVERY SEAL.
PERFORMANCE IN EVERY PACK.



www.rotomakeengineering.com



sales@rotomakeengineering.com



TECHNICAL SPECIFICATIONS

ENGINEERED FOR RELIABLE PACKAGING PERFORMANCE

PARAMETER	SPECIFICATION
 Machine / Application	1.25 LTR Web Sealer with Shrink Wrapping
 Operating Mode	Semi Automatic
 Sealing Method	Hot Knife Technology
 Maximum Sealing Width	530 mm
 Tunnel Size	39" × 18" × 12"
 Cooling Chamber	13" × 18" × 12"
 Body	M.S. Powder Coated
 Speed Control	Variable – AC Drive
 Main Motor	0.5 HP, 3 Phase
 Blower Motor	0.18 HP, 3 Phase, 2800 RPM – 1 No.
 Cooling Motor	12", 1440 RPM – 1 No.
 Heater	30" Long – 9 Nos.
 Conveyor	SS 304 Mesh Type
 Electrical Requirement	440 VAC
 Power	10 kW
 Temperature Controller	Selec TC-513
 Timer Meter	Solar 4408N
 Switches	L&T; and Autonics
 M.C.B.	L&T;
 Cylinder	Janatics – 4 Nos.
 Solenoid Valve	Janatics 220 V – 3 Nos.
 FRL	Janatics
 Pneumatics	Janatics
 Air Requirement	6 LPM @ 6 bar
 Insulation	Cerawool
 Wiring	Fiberglass + Teflon Coated
 Packing Speed – 200 ml	4 Pack of 48 bottles/min (192 bottles/min)
 Packing Speed	4 Pack of 24 bottles/min (96 bottles/min)
 Packing Speed	5 Pack of 12 bottles/min (60 bottles/min)
 Web Sealer Dimensions	30" × 34" × 74"
 Shrink Machine Dimensions	72" × 26" × 58"
Approx. Weight	400 kg

